



No.2262B

2SA1552/2SC4027

PNP/NPN Epitaxial Planar Silicon Transistors

High-Voltage Switching Applications

Applications

- Converters, inverters, color TV audio output

Features

- Adoption of FBET, MBET processes
- High voltage and large current capacity
- Fast switching time
- Small and slim package permitting 2SA1552/2SC4027-applied sets to be made more compact

(): 2SA1552

Absolute Maximum Ratings at Ta=25°C

			unit
Collector to Base Voltage	V _{CB0}	(-)180	V
Collector to Emitter Voltage	V _{CEO}	(-)160	V
Emitter to Base Voltage	V _{EBO}	(-)6	V
Collector Current	I _C	(-)1.5	A
Collector Current(Pulse)	I _{CP}	(-)2.5	A
Collector Dissipation	P _C	1	W
	P _C	15	W
Junction Temperature	T _j	150	°C
Storage Temperature	T _{stg}	-55 to +150	°C

Tc=25°C

Electrical Characteristics at Ta=25°C

			min	typ	max	unit
Collector Cutoff Current	I _{CB0}	V _{CB} =(-)120V, I _E =0			(-)1.0	µA
Emitter Cutoff Current	I _{EBO}	V _{EB} =(-)4V, I _C =0			(-)1.0	µA
DC Current Gain	h _{FE} (1)	V _{CE} =(-)5V, I _C =(-)100mA	100*		400*	
	h _{FE} (2)	V _{CE} =(-)5V, I _C =(-)10mA	80			
Gain-Bandwidth Product	f _T	V _{CE} =(-)10V, I _C =(-)50mA		120		MHz
Output Capacitance	c _{ob}	V _{CB} =(-)10V, f=1MHz		(22)12		pF


Continued on next page.

*: The 2SA1552/2SC4027 are classified by 100mA h_{FE} as follows:

100 R	200	140 S	280	200 T	400
-------	-----	-------	-----	-------	-----


Package Dimensions 2045B

(unit: mm)



Package Dimensions 2044B

(unit: mm)




SANYO Electric Co., Ltd. Semiconductor Business Headquarters

TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN

Continued from preceding page.





			min	typ	max	unit
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C=(-)500mA, I_B=(-)50mA$	(-0.2)	(-0.5)		V
B-E Saturation Voltage	$V_{BE(sat)}$	$I_C=(-)500mA, I_B=(-)50mA$	(-)0.85	(-)1.2		V
C-B Breakdown Voltage	$V_{(BR)CBO}$	$I_C=(-)10\mu A, I_E=0$	(-)180			V
C-E Breakdown Voltage	$V_{(BR)CEO}$	$I_C=(-)1mA, R_{BE}=\infty$	(-)160			V
E-B Breakdown Voltage	$V_{(BR)EBO}$	$I_E=(-)10\mu A, I_C=0$	(-)6			V
Turn-on Time	t_{on}	See specified Test Circuit.		60		ns
Storage Time	t_{stg}			(0.7)1.2		μs
Fall Time	t_f			(50)80		ns

Switching Time Test Circuit











$10|I_{B1}| = -10|I_{B2}| = I_C = 0.7A$
For PNP, the polarity is reversed.





Unit (Resistance : Ω , Capacitance : F)



2SA1552/2SC4027



2SA1552/2SC4027



- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.