



CHENMKO ENTERPRISE CO.,LTD

CH221PT

**SURFACE MOUNT
SWITCHING DIODE**

VOLTAGE 20 Volts CURRENT 0.1 Ampere

Lead free devices

APPLICATION

- * Bias circuit.
- * Protection circuits.

FEATURE

- * Small surface mounting type. (SC-75/SOT-416)
- * Two diode elements are connected in series (VFX2) per circuit.
- * Maximum total power dissipation is 150mW.
- * Peak forward current is 200mA.

CONSTRUCTION



- * Silicon epitaxial planar

MARKING

- * A7




SC-75/SOT-416



Dimensions in millimeters

SC-75/SOT-416

CIRCUIT



MAXIMUM RATINGS (At TA = 25°C unless otherwise noted)

RATINGS	SYMBOL	CH221PT	UNITS
Maximum Recurrent Peak Reverse Voltage	VRRM	20	Volts
Maximum RMS Voltage	VRMS	14	Volts
Maximum DC Blocking Voltage	VDC	20	Volts
Maximum Average Forward Rectified Current	IO	0.1	Amps
Peak Forward Surge Current at 1uSec.	IFSM	0.3	Amps
Typical Junction Capacitance between Terminal (Note 1)	CJ	2.0	pF
Maximum Operating Temperature Range	TJ	+150	°C
Storage Temperature Range	TSTG	-55 to +150	°C

ELECTRICAL CHARACTERISTICS (At TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	CH221PT	UNITS
Maximum Instantaneous Forward Voltage at IF= 10mA	VF	1.00	Volts
Maximum Average Reverse Current at VR= 15V	IR	0.1	uAmps

NOTES : 1. Measured at 1.0 MHz and applied reverse voltage of 6.0 volts.
2. ESD sensitive product handling required.

RATING CHARACTERISTIC CURVES (CH221PT)

FIG. 1 - FORWARD CHARACTERISTICS




FIG. 2 - FORWARD CHARACTERISTICS




FIG. 3 - REVERSE CHARACTERISTICS




FIG. 4 - TYPICAL JUNCTION CAPACITANCE

