
BB721

Tuner Diodes

SOD-123



Dimensions in inches and (millimeters)

FEATURES

- Silicon epitaxial planar capacitance diodes with very wide effective capacitance variation for tuning the whole range of UHF television bands.
- ♦ Two BB721/BB721S tuner diodes in series are used for direct satellite receivers.
- These diodes are available as singles or as matched sets of two or more units according to the tracking condition described in the table of characteristics.
- ♦ This diode is also available in SOD-323 case with the type designation BB721S.

MECHANICAL DATA

Case: SOD-123 Plastic Case Weight: approx. 0.01 g

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified

	Symbol	Value	Unit
Reverse Voltage	V _R	32	V
Ambient Temperature	T _{amb}	125	°C
Storage Temperature Range	T _S	-55 to +125	°C



BB721

ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified


	Symbol	Min.	Тур.	Max.	Unit
Reverse Breakdown Voltage at I _R = 100 μA	V _{(BR)R}	32	_	-	V
Leakage Current at V _R = 30 V	I _R	-	-	10	nA
Capacitance $f = 1$ MHz at $V_R = 28$ V at $V_R = 1$ V	C _{tot} C _{tot}	1.9 17.5	-	2.3 20	pF pF
Effective Capacitance Ratio, f = 1 MHz at V _R = 1 to 28 V	C _{tot} (1 V) C _{tot} (28V)	8.2	-	9.8	-
Series Resistance at f = 470 MHz, C _{tot} = 14 pF	r _s	_	0.55	-	Ω
Series Inductance	L _s	_	2.5	-	nH

For any two of six consecutive diodes in the carrier tape, the maximum capacitance deviation in the reverse bias voltage of $V_R = 0.5$ to 28 V is max. 2.5%.




RATINGS AND CHARACTERISTIC CURVES BB721


Capacitance versus reverse voltage




Relative capacitance versus junction temperature



Temperature coefficient of capacitance versus reverse voltage



Leakage current versus reverse voltage





RATINGS AND CHARACTERISTIC CURVES BB721

Q-Factor versus frequency

