

## NC7NZ04 TinyLogic® UHS Inverter

### General Description

The NC7NZ04 is a triple inverter from Fairchild's Ultra High Speed Series of TinyLogic®. The device is fabricated with advanced CMOS technology to achieve ultra high speed with high output drive while maintaining low static power dissipation over a very broad  $V_{CC}$  operating range. The device is specified to operate over the 1.65V to 5.5V  $V_{CC}$  range. The inputs and output are high impedance when  $V_{CC}$  is 0V. Inputs tolerate voltages up to 7V independent of  $V_{CC}$  operating voltage.


### Features

- Space saving US8 surface mount package
- MicroPak™ leadless package
- Ultra High Speed;  $t_{PD}$  2.4 ns typ into 50 pF at 5V  $V_{CC}$
- High Output Drive;  $\pm 24$  mA at 3V  $V_{CC}$
- Broad  $V_{CC}$  Operating Range: 1.65V to 5.5V
- Power down high impedance inputs/output
- Overvoltage tolerant inputs facilitate 5V to 3V translation
- Patented noise/EMI reduction circuitry implemented

### Ordering Code:

| Order Number | Package Number | Product Code Top Mark | Package Description                               | Supplied As               |
|--------------|----------------|-----------------------|---|---------------------------|
| NC7NZ04K8X   | MAB08A         | 7NZ04                 | 8-Lead US8, JEDEC MO-187, Variation CA 3.1mm Wide | 3k Units on Tape and Reel |
| NC7NZ04L8X   | MAC08A         | T3                    | 8-Lead MicroPak, 1.6 mm Wide                      | 5k Units on Tape and Reel |

### Logic Symbol



### Pin Descriptions

| Pin Names | Description |
|-----------|-------------|
| A         | Input       |
| Y         | Output      |

### Function Table


$$Y = \bar{A}$$

| Input | Output |
|-------|--------|
| A     | Y      |
| L     | H      |
| H     | L      |


H = HIGH Logic Level  
L = LOW Logic Level

TinyLogic® is a registered trademark of Fairchild Semiconductor Corporation.  
MicroPak™ is a trademark of Fairchild Semiconductor Corporation.

### Connection Diagrams




(Top View)



AAA represents Product Code Top Mark - see ordering code  
**Note:** Orientation of Top Mark determines Pin One location. Read the Top Product Code Mark left to right, Pin One is the lower left pin (see diagram).

### Pad Assignments for MicroPak



(Top Thru View)

**Absolute Maximum Ratings**(Note 1)

|  |                 |
|--|-----------------|
| Supply Voltage ( $V_{CC}$ )                  | -0.5V to +7V    |
| DC Input Voltage ( $V_{IN}$ )                | -0.5V to +7V    |
| DC Output Voltage ( $V_{OUT}$ )              | -0.5V to +7V    |
| DC Input Diode Current ( $I_{IK}$ )          |                 |
| @ $V_{IN} < -0.5V$                           | -50 mA          |
| @ $V_{IN} > 6V$                              | +20 mA          |
| DC Output Diode Current ( $I_{OK}$ )         |                 |
| @ $V_{OUT} < -0.5V$                          | -50 mA          |
| @ $V_{OUT} > 6V, V_{CC} = GND$               | +20 mA          |
| DC Output Current ( $I_{OUT}$ )              | $\pm 50$ mA     |
| DC $V_{CC}/GND$ Current ( $I_{CC}/I_{GND}$ ) | $\pm 50$ mA     |
| Storage Temperature ( $T_{STG}$ )            | -65°C to +150°C |
| Junction Temperature under Bias ( $T_J$ )    | 150°C           |
| Junction Lead Temperature ( $T_L$ )          |                 |
| (Soldering, 10 seconds)                      | 260°C           |
| Power Dissipation ( $P_D$ ) @ +85°C          | 250 mW          |

**Recommended Operating Conditions** (Note 2)

|  |                   |
|--|-------------------|
| Supply Voltage Operating ( $V_{CC}$ )      | 1.65V to 5.5V     |
| Supply Voltage Data Retention ( $V_{CC}$ ) | 1.5V to 5.5V      |
| Input Voltage ( $V_{IN}$ )                 | 0V to 5.5V        |
| Output Voltage ( $V_{OUT}$ )               | 0V to $V_{CC}$    |
| Operating Temperature ( $T_A$ )            | -40°C to +85°C    |
| Input Rise and Fall Time ( $t_r, t_f$ )    |                   |
| $V_{CC} = 1.8V, 2.5V \pm 0.2V$             | 0 ns/V to 20 ns/V |
| $V_{CC} = 3.3V \pm 0.3V$                   | 0 ns/V to 10 ns/V |
| $V_{CC} = 5.0V \pm 0.5V$                   | 0 ns/V to 5 ns/V  |
| Thermal Resistance ( $\theta_{JA}$ )       | 250°C/W           |

**Note 1:** Absolute maximum ratings are DC values beyond which the device may be damaged or have its useful life impaired. The datasheet specifications should be met without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. Fairchild does not recommend operation outside datasheet specifications.

**Note 2:** Unused inputs must be held HIGH or LOW. They may not float.

**DC Electrical Characteristics**

| Symbol    | Parameter                 | $V_{CC}$<br>(V)              | $T_A = +25^\circ C$           |      |      | $T_A = -40^\circ C$ to $+85^\circ C$ |     | Units             | Conditions  |  |
|-----------|---------------------------|------------------------------|-------------------------------|------|------|--------------------------------------|-----|-------------------|---|--|
|           |                           |                              | Min                           | Typ  | Max  | Min                                  | Max |                   |   |  |
| $V_{IH}$  | HIGH Level Input Voltage  | 1.8 $\pm$ 0.15<br>2.3 to 5.5 | 0.75 $V_{CC}$<br>0.7 $V_{CC}$ |      |      | 0.75 $V_{CC}$<br>0.7 $V_{CC}$        |     | V                 |   |  |
| $V_{IL}$  | LOW Level Input Voltage   | 1.8 $\pm$ 0.15<br>2.3 to 5.5 | 0.25 $V_{CC}$<br>0.3 $V_{CC}$ |      |      | 0.25 $V_{CC}$<br>0.3 $V_{CC}$        |     | V                 |   |  |
| $V_{OH}$  | HIGH Level Output Voltage | 1.65                         | 1.55                          | 1.65 | 1.55 |                                      | V   | $V_{IN} = V_{IL}$ | $I_{OH} = -100 \mu A$   |  |
|           |                           | 2.3                          | 2.2                           | 2.3  | 2.2  |                                      |     |                   |   |  |
|           |                           | 3.0                          | 2.9                           | 3.0  | 2.9  |                                      |     |                   |   |  |
|           |                           | 4.5                          | 4.4                           | 4.5  | 4.4  |                                      |     |                   |   |  |
|           |                           | 1.65                         | 1.29                          | 1.52 | 1.29 |                                      | V   |                   | $I_{OH} = -4$ mA<br>$I_{OH} = -8$ mA<br>$I_{OH} = -16$ mA<br>$I_{OH} = -24$ mA<br>$I_{OH} = -32$ mA |  |
|           |                           | 2.3                          | 1.9                           | 2.15 | 1.9  |                                      |     |                   |   |  |
|           |                           | 3.0                          | 2.4                           | 2.80 | 2.4  |                                      |     |                   |   |  |
|           |                           | 3.0                          | 2.3                           | 2.68 | 2.3  |                                      |     |                   |   |  |
| 4.5       | 3.8                       | 4.20                         | 3.8                           |      |      |                                      |     |                   |   |  |
| $V_{OL}$  | LOW Level Output Voltage  | 1.65                         | 0.0                           |      | 0.1  | 0.1                                  |     | V                 | $V_{IN} = V_{IH}$   | $I_{OL} = 100 \mu A$   |
|           |                           | 2.3                          | 0.0                           |      | 0.1  | 0.1                                  |     |                   |   |  |
|           |                           | 3.0                          | 0.0                           |      | 0.1  | 0.1                                  |     |                   |   |  |
|           |                           | 4.5                          | 0.0                           |      | 0.1  | 0.1                                  |     |                   |   |  |
|           |                           | 1.65                         | 0.08                          |      | 0.24 | 0.24                                 |     | V                 |   | $I_{OL} = 4$ mA<br>$I_{OL} = 8$ mA<br>$I_{OL} = 16$ mA<br>$I_{OL} = 24$ mA<br>$I_{OL} = 32$ mA |
|           |                           | 2.3                          | 0.10                          |      | 0.3  | 0.3                                  |     |                   |   |  |
|           |                           | 3.0                          | 0.15                          |      | 0.4  | 0.4                                  |     |                   |   |  |
|           |                           | 3.0                          | 0.22                          |      | 0.55 | 0.55                                 |     |                   |   |  |
| 4.5       | 0.22                      |                              | 0.55                          | 0.55 |      |                                      |     |                   |   |  |
| $I_{IN}$  | Input Leakage Current     | 0 to 5.5                     | $\pm 0.1$                     |      |      | $\pm 1.0$                            |     | $\mu A$           | $0 \leq V_{IN} \leq 5.5V$   |  |
| $I_{OFF}$ | Power Off Leakage Current | 0.0                          | 1                             |      |      | 10                                   |     | $\mu A$           | $V_{IN}$ or $V_{OUT} = 5.5V$  |  |
| $I_{CC}$  | Quiescent Supply Current  | 1.65 to 5.5                  | 1.0                           |      |      | 10                                   |     | $\mu A$           | $V_{IN} = 5.5V, GND$  |  |

## AC Electrical Characteristics


| Symbol           | Parameter                        | V <sub>CC</sub><br>(V) | T <sub>A</sub> = +25°C |     |     | T <sub>A</sub> = -40°C to +85°C |     | Units | Conditions                                      | Figure Number |
|------------------|----------------------------------|------------------------|------------------------|-----|-----|---------------------------------|-----|-------|---|---------------|
|                  |                                  |                        | Min                    | Typ | Max | Min                             | Max |       |   |               |
| t <sub>PLH</sub> | Propagation Delay                | 1.8 ± 0.15             | 1.8                    | 4.4 | 9.5 | 2.0                             | 10  | ns    | C <sub>L</sub> = 15 pF<br>R <sub>L</sub> = 1 MΩ | Figures 1, 3  |
| t <sub>PHL</sub> |                                  | 2.5 ± 0.2              | 0.8                    | 2.9 | 5.1 | 0.8                             | 5.6 |       |   |               |
|                  |                                  | 3.3 ± 0.3              | 0.5                    | 2.1 | 3.4 | 0.5                             | 3.8 |       |   |               |
|                  |                                  | 5.0 ± 0.5              | 0.5                    | 1.8 | 2.8 | 0.5                             | 3.1 |       |   |               |
| t <sub>PLH</sub> | Propagation Delay                | 3.3 ± 0.3              | 1.2                    | 2.9 | 4.5 | 1.2                             | 5.0 | ns    | C <sub>L</sub> = 50 pF<br>R <sub>L</sub> = 500Ω | Figures 1, 3  |
| t <sub>PHL</sub> |                                  | 5.0 ± 0.5              | 0.8                    | 2.4 | 3.6 | 0.8                             | 4.0 |       |   |               |
| C <sub>IN</sub>  | Input Capacitance                | 0                      | 2.5                    |     |     |                                 |     | pF    |   |               |
| C <sub>PD</sub>  | Power Dissipation<br>Capacitance | 3.3<br>5.0             | 9<br>11                |     |     |                                 |     | pF    | (Note 3)  | Figure 2      |

**Note 3:** C<sub>PD</sub> is defined as the value of the internal equivalent capacitance which is derived from dynamic operating current consumption (I<sub>CCD</sub>) at no output loading and operating at 50% duty cycle. (See Figure 2.) C<sub>PD</sub> is related to I<sub>CCD</sub> dynamic operating current by the expression:  
I<sub>CCD</sub> = (C<sub>PD</sub>) (V<sub>CC</sub>) (f<sub>IN</sub>) + (I<sub>CC</sub> static)

## Dynamic Switching Characteristics


| Symbol           | Parameter                                   | Conditions  | V <sub>CC</sub><br>(V) | T <sub>A</sub> = 25°C | Unit |
|------------------|---|---|------------------------|-----------------------|------|
|                  |   |   |                        | Typical               |      |
| V <sub>OLP</sub> | Quiet Output Dynamic Peak V <sub>OL</sub>   | C <sub>L</sub> = 50pF, V <sub>IH</sub> = 5.0V, V <sub>IL</sub> = 0V | 5.0                    | 0.8                   | V    |
| V <sub>OLV</sub> | Quiet Output Dynamic Valley V <sub>OL</sub> | C <sub>L</sub> = 50pF, V <sub>IH</sub> = 5.0V, V <sub>IL</sub> = 0V | 5.0                    | -0.8                  | V    |

## AC Loading and Waveforms




C<sub>L</sub> includes load and stray capacitance  
Input PRR = 1.0 MHz, t<sub>W</sub> = 500 ns

**FIGURE 1. AC Test Circuit**



Input = AC Waveform; t<sub>r</sub> = t<sub>f</sub> = 1.8 ns;  
PRR = 10 MHz; Duty Cycle = 50%


**FIGURE 2. I<sub>CCD</sub> Test Circuit**



**FIGURE 3. AC Waveforms**





**Tape and Reel Specification** (Continued)  
**REEL DIMENSIONS** inches (millimeters)






| Tape Size | A              | B               | C                | D                | N                | W1   | W2               | W3                                     |
|-----------|----------------|-----------------|------------------|------------------|------------------|--|------------------|--|
| 8 mm      | 7.0<br>(177.8) | 0.059<br>(1.50) | 0.512<br>(13.00) | 0.795<br>(20.20) | 2.165<br>(55.00) | 0.331 + 0.059/-0.000<br>(8.40 + 1.5/-0.00) | 0.567<br>(14.40) | W1 + 0.078/-0.039<br>(W1 + 2.00/-1.00) |

**Physical Dimensions** inches (millimeters) unless otherwise noted



**LAND PATTERN RECOMMENDATION**



**DETAIL A**


**NOTES:**

- A. CONFORMS TO JEDEC REGISTRATION MO-187
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
- D. DIMENSIONS AND TOLERANCES PER ANSI Y14.5M, 1982.

MAB08AREVC

**8-Lead US8, JEDEC MO-187, Variation CA 3.1mm Wide  
Package Number MAB08A**

**Physical Dimensions** inches (millimeters) unless otherwise noted (Continued)



- Notes:
1. PACKAGE REGISTRATION WITH JEDEC IS ANTICIPATED
  2. DIMENSIONS ARE IN MILLIMETERS
  3. DRAWING CONFORMS TO ASME Y.14M-1994

MAC08AREVB

**8-Lead MicroPak, 1.6 mm Wide  
Package Number MAC08A**

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

**LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)