

MA2S331

Silicon epitaxial planar type


For VCO of an UHF radio

■ Features

- Small series resistance r_D , $r_D = 0.18 \Omega$ (typ.)
- Good linearity of $C - V$ curve
- SS-mini package, optimum for down-sizing of equipment

■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

| Parameter | Symbol | Rating | Unit |
|----------------------|-----------|-------------|------------------|
| Reverse voltage (DC) | V_R | 12 | V |
| Forward current (DC) | I_F | 20 | mA |
| Junction temperature | T_j | 150 | $^\circ\text{C}$ |
| Storage temperature | T_{stg} | -55 to +150 | $^\circ\text{C}$ |



Marking Symbol: F

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|----------------------|------------------------|---|------|------|------|----------|
| Reverse current (DC) | I_R | $V_R = 12 \text{ V}$ | | | 10 | nA |
| Diode capacitance | $C_{D(1V)}$ | $V_R = 1 \text{ V}, f = 1 \text{ MHz}$ | 17.0 | | 20.0 | pF |
| | $C_{D(2V)}$ | $V_R = 2 \text{ V}, f = 1 \text{ MHz}$ | 14.0 | 15.0 | 16.0 | pF |
| | $C_{D(4V)}$ | $V_R = 4 \text{ V}, f = 1 \text{ MHz}$ | 10.0 | | 12.4 | pF |
| | $C_{D(10V)}$ | $V_R = 10 \text{ V}, f = 1 \text{ MHz}$ | 5.5 | 6.0 | 6.5 | pF |
| Capacitance ratio | $C_{D(1V)}/C_{D(4V)}$ | | 1.53 | 1.6 | 1.83 | — |
| | $C_{D(2V)}/C_{D(10V)}$ | | 2.25 | 2.5 | 2.75 | — |
| Series resistance* | r_D | $C_D = 9 \text{ pF}, f = 470 \text{ MHz}$ | | 0.18 | 0.22 | Ω |

Note) 1. Rated input/output frequency: 470 MHz

2. *: r_f measuring instrument: YHP MODEL 4191A RF IMPEDANCE ANALYZER

