



产品特点 FEATURES

- 低功耗，宽频率范围 Low current and wide frequency range
- 小型、超薄式 (5.0×3.2×1.2 mm) Small size and ultra-thin (5.0×3.2×1.2 mm)
- 宽温度范围应用 (-40℃~85℃) Wide operating temperature range
- 贴片、无铅 SMD Leadless
- 金属密封，具有高可靠性能 Metal seam sealing reaches high reliability


标准规格 STAND SPECIFICATIONS

频率范围	Out Frequency Range	F0	1.000~50.000 MHz				
频率稳定度	Frequency Stability	$\Delta f / F$	±50ppm max. (±5ppm, ±10ppm, ±20ppm, ±30ppm)				
工作温度	Operating Temperature	T _{opr}	-20℃~+70℃ (other operating range is available)				
频率温度特性	Frequency Stability Over Temperature	Ftem	±50ppm max. (±5ppm, ±10ppm, ±20ppm, ±30ppm)				
储存温度范围	Storage Temperature Range	T _{sto}	-40℃ ~ +85℃				
工作电压	Supply Voltage	Vdd	1.8V or	2.8V	3.0V	3.3V	5.0V
工作电流	Current Consumption	I _{dd}	10mA max (f0≤40MHz)				
输出波形	Level Output Voltage	Vol max, Voh min	0.1VDD , 0.9VDD				
占空比	Symmetry min. to max.	%	45 to 55				
负载电容	Load Capacitance	CMOS, TTL	15PF , (1~10) TTL				
上下降沿	Rise and Fall Time	Tr, Tf	8ns max. (f0≤40MHz)				
启动时间	Start-up Time	T _{st}	10ms max.				
年老化	Ageing (at 25℃)	Fage	3ppm/ year Max.				


Note: Specified a product with specification is welcome, please contact our sales representative.

注：可按客户参数要求定制产品。

外形尺寸 DIMENSIONS



回流焊 REFLOW CONDITION



使用须知 NOTICE FOR USE

The content given above in this data sheet might be updated without prior notice. If you don't have an advance notice, please confirm with our sales.

在没有通知的情况下，以上产品可能会更新升级。请联系我们了解具体的相关产品。