



产品特点 FEATURES

- 低功耗，宽频率范围 Low current and wide frequency range
- 小型、超薄式 (5.0×3.2×1.0 mm) Small size and ultra-thin (5.0×3.2×1.0 mm)
- 贴片、无铅 SMD Leadless
- 金属密封，具有高可靠性 Metal seam sealing reaches high reliability

标准规格 STAND SPECIFICATIONS



频率范围	Out Frequency Range	F0	1.000~80.000 MHz		
频率稳定度	Frequency Stability	$\Delta f / F$	±50ppm max. (±5ppm, ±10ppm, ±20ppm, ±30ppm)		
频率控制电压	Frequency Voltage	Vcont	1.5±1.0V	1.65±1.35V	2.5±2.0V
频率牵引范围	Frequency Adjustment Range	Fvcon	±90ppm min. (Positive Slop)		
工作温度	Operating Temperature	T _{opr}	20°C ~+70°C (other operating is available)		
频率温度特性	Frequency Stability Over Temperature *3	Ftem	±50ppm max. (±5ppm, ±10ppm, ±20ppm, ±30ppm)		
储存温度范围	Storage Temperature Range	T _{str}	-40°C ~ +85°C		
工作电压	Supply Voltage	Vdd	3.0V	3.3V	5.0V
工作电流	Current Consumption	Idd	10mA max		15mA max
输出波形	Level Output Voltage	V _{ol} max, V _{oh} min	0.1VDD , 0.9VDD		
占空比	Symmetry min. to max.	%	45 to 55		
负载	Load	CMOS, TTL	15PF , (1~10) TTL		
上下降沿	Rise and Fall Time	Tr, Tf	8ns max. (f0≤40MHz)		
启动时间	Start-up Time	ST	10ms max.		
年老化	Ageing (at 25°C)	Fage	3ppm/ year Max.		

Note: Specified a product with specification is welcome, please contact our sales representative.

注：可按客户参数要求定制产品。

外形尺寸 DIMENSIONS

回流焊 REFLOW CONDITION



使用须知 NOTICE FOR USE

The content given above in this data sheet might be updated without prior notice. If you don't have an advance notice, please confirm with our sales.

在没有通知的情况下，以上产品可能会更新升级。请联系我们了解具体的相关产品。